

HOLTKÖTTER®

The Ultimate Lighting Machines™

205 Hardman Avenue South, South Saint Paul, MN 55075
Voice: (800) 899-5444 • Fax: (888) 552-8661
e-mail: customerservice@holtkoetter.com
www.holtkoetter.com





Please make sure that the following parts for ceiling fixture are enclosed:

1. Fixture including backplate & LEDs
2. Glass shade

Be sure to turn off the circuit breaker before installing this fixture. It is recommended that this fixture be installed and hung by a licensed electrician.

Mounting Instructions

1. Disconnect power to the outlet box before installation.
2. Loosen screw (A) to release the fixture from the backplate (B).
3. Mount the backplate (B) to the outlet box.
4. Connect the wires from the fixture with the wires in the outlet box according to generally accepted electrical standards.
5. Slip the fixture onto the backplate (B). Using a phillips head screwdriver, secure the fixture to the outlet box by tightening the screw (A).



Install the Glass Shade

1. Install the glass shade on the fixture, centering the aluminum nut (C) on the fixture.
2. OPTIONAL: If desired, the glass can be lowered by installing the additional plastic washers provided. Prior to installation, set one or two washers on the aluminum screw inside the glass shade.
3. Using the 5mm hex key (D) provided, screw the glass shade onto the middle stem of the fixture. Hand-tighten to secure the glass to the fixture. Do not overtighten.
4. Install the finished disc (E) by screwing it into place in the center of the aluminum nut (C).

LED Specifications

3502*LED: 1x ZEGA LED (120V/29W), 3000 Lumens (equivalency to 250W Osram Halogen), 3000K/CRI 80+

3503*LED: 2x ZEGA LED (120V/40W), 3600 Lumens (equivalency to 300W Osram Halogen), 3000K/CRI 80+

3505*LED: 1x ZEGA LED (120V/58W), 5000 Lumens (equivalency to 400W Osram Halogen), 3000K/CRI 80+

ASSEMBLY INSTRUCTIONS FOR

LED Ceiling Fixtures

No. 3502*LED, No. 3503*LED & No. 3505*LED



Care Instructions

Use only a soft, dry cloth to clean. If necessary, a slightly damp, soft cloth can be used to spot clean. Do not use common household cleaners on lamps or fixtures, as the lacquer on the outside of the brass may be damaged as a result. Enjoy your new Holtkötter fixture.